



# KR11 Plus Series

(1-10kVA)

- » Data center
- » Point-of-sale
- » Network device
- » Commercial facility
- » Precision instrument

## Green Power:


- Input power factor up to 0.996, low THDi (< 5%), decrease pollution to city power
- AC/AC efficiency up to 95%, energy saving and low carbon emission
- Compliance with RoHS standard, innocuous and environmental friendly
- Design in accordance to International EMC and Safety standard

## Outstanding Profitability:

- Minimum 0.05m<sup>2</sup> footprint, save delivery cost and easy for installation

## Excellent Flexibility:

- Output voltage and ECO mode are selectable via LCD
- 1~8A charging current settable via software (6-10KVA)
- Batteries quantity are settable (16/17/18/19/20 for 6-10kVA)
- Maintenance bypass for 6-10KVA (option)
- Battery disconnection alarm (option)
- SNMP or RS485+dry contact (option)
- Charging voltage temperature compensation (option)



## Available Socket:



### Technical Specification

MODEL	KR1000+/ KR1000L+	KR2000+/ KR2000L+	KR3000+/ KR3000L+	KR6000+/ KR6000L+	KR1110S+/ KR1110+
<b>Input</b>					
Voltage (Vac)	120~295			80~275	
Frequency (Hz)	50/60± 10% (50/60Hz auto-sensing)				
Power Factor	≥0.99				
THDi	<5%				
<b>Output</b>					
Capacity (VA)	1000	2000	3000	6000	10000
Max. AC/AC Efficiency	92%	93%	94%	95%	95%
Power Factor	0.9 (1.0 optional)				
Voltage (Vac)	208/220/230/240±1% ( selectable on display panel )				
Frequency (Hz)	50/60±0.2% (battery mode)				
THDv	THD < 2% (linear load ); THD < 5% (nonlinear load )			THD < 1% (linear load ); THD < 4% (nonlinear load )	
Transfer Time (ms)	0				
<b>Battery</b>					
Voltage (Vdc)	24 or 36/36	48 or 72/72	72 or 96/96	192/192~240	192/192~240
BATT Type	2×9Ah 12V or 3×7Ah 12V/ External	4×9Ah 12V or 6×7Ah 12V/ External	6×9Ah 12V or 8×7Ah 12V/ External	16×7Ah 12V/ External (16~20 units settable)	16×9Ah 12V/ External (16~20 units settable)
Charger Current (A) Max.	1/4	1/4	1/4	1~8 (adjustable)	1~8 (adjustable)
<b>Other</b>					
Communication Interface	RS232, EPO, USB (slot) (SNMP, RS485+dry contact are optional in slot)				
LCD Display	AC input & output voltage, frequency, Load level, battery level, temperature; AC mode, battery mode, bypass mode, and fault				
Alarm	Low battery, abnormal AC input, UPS failure, etc.				
Protection	Low battery, overload, short-circuit and over temperature, etc.				
Noise (dB)	<50	<55			
Working Temperature (°C)	-5~40				
Relative Humidity	0 ~ 95%, no condensation				
Dimension (W×D×H) mm	145×360×225	190×400×330		230×502×553/190×422×337	
Weight (kg)	9.2 or 11.6/4.5	17.7 or 22.4/8.5	22.9 or 27.6/9.2	54.5/10.9	56.2/12.5

\* Specification is subject to change without prior notice

**KEHUA France SAS**

www.kehua-france.com

3 place du général de Gaulle - 13001 Marseille

Tel. +33 (0)4 65 38 62 48

